

Pneumatic breaker (Hex 28x160) (1 1/8x6).Not sold for use within EEA (European Economic Area).

■ T E X P 6 0

8461 0227 20



[Create PDF sheet](#)

[Request information](#)

Atlas Copco Construction Equipment
800 732 6762
[Send an email](#)

Quick links

[Atlas Copco Print Shop](#)
[Atlas Copco Photo Archive](#)

Product information

TEX P60 and TEX P90 were developed to meet the tough requirements found, for example, in the rental industry. TEX P60 is ideal for breaking asphalt, while the TEX P90 is our most powerful demolition breaker, especially suitable for breaking hard reinforced concrete or other tasks where real power is required.

Features & benefits

- Solid Body concept
- SOFSTART™ two-step trigger
- Rotating air inlet swivel
- Integrated lubricator
- Air cushioned piston

Applications

- General demolition
- For use in medium and hard materials
- TEX P60: Asphalt and other medium soft materials
- TEX P90: Hard / Reinforced concrete

Technical data

Units: [Metric](#) | [Imperial](#)

Technical Specifications	
Breaker type	Standard
Breaker Version	
Shank Size (mm)	
Shank Size (inch)	
Weight	68 lb
Length	27 5/32 inch
Air consumption	76 cfm
Impact Rate	1500 blows/min