

Rivet Buster



Features

- deep case-hardened alloy steel cylinder
- uses jumbo extra heavy duty tool steel
- heavy duty upper and lower sleeves
- adjustable exhaust deflector
- teflon throttle valve

Model 633

- 6" stroke
- drop forged D-style handle
- inside trigger for better control and safety

Model 133/Model 1133

- 8" stroke/11" stroke
- drop forged D-style handle
- inside trigger for better control and safety

*Model 1433

- 14" stroke
- drop forged D-style handle
- inside trigger for better control and safety
- innovative lightweight cylinder design

*Special orders of 25 or more only.

Model	Bore	Stroke	B.P.M.	CFM @90PSI	Weight lbs.	Length in.	Air Inlet NPT
633	1-3/16	6	1100	42-46	24	20-5/8	3/8 female
133	1-3/16	8	1140	42-46	30	22-1/2	3/8 female
1133	1-3/16	11	850	48-52	33	25-1/2	3/8 female
1433	1-3/16	14	600	49-53	34	28-5/8	3/8 female

Clay and Trench Diggers



Features

- deep case-hardened alloy steel cylinders
- replaceable chuck bushing
- latch-type retainer

Model 118 Clay Digger

- built-in automatic oiler
- D-style handle
- inside trigger for better control and safety
- automatic valve

Model 119 Trench Digger

- built-in automatic oiler
- T-style forged handle
- rubber handle grips
- automatic valve

Model 125 Clay Digger

- D-style handle
- inside trigger for better control and safety
- flapper valve design allows dirt to pass without stopping tool
- replaceable chuck and piston stem bushing

Backfill Tamper



Model 131

- built-in large automatic oiler
- flapper valve design allows dirt to pass without stopping the tool
- internally reinforced large malleable iron butt (standard)
- pole butt (half-moon), and 3" diameter butts available

Model	131
Bore	1-1/2
Stroke	5-1/2
B.P.M.	670
CFM @90PSI	38-42
Weight lbs.	37
Length in.	51-7/8
Air Inlet NPT	1/2 female

Model	Chuck Size	Bore	Stroke	B.P.M.	CFM @90PSI	Weight lbs.	Length in.	Air Inlet NPT
118	7/8x3-1/4 • 1x4-1/4	1-3/4	3-3/8	1850	34-36	31	22-1/2	3/8 male
119	7/8x3-1/4 • 1x4-1/4	1-3/4	3-3/8	1850	34-38	37	31	1/2 female
125	7/8 hex x 3-1/4	1-11/16	2-3/4	2120	38-42	21	18-3/8	3/8 female