

P-210

PROFESSIONAL PNEUMATIC HARDWOOD FLOORING NAILER

The Primatech P-210 pneumatic hardwood flooring nailer is powerful, productive and lightweight for easy maneuverability. Its aluminum construction allows for durability. Primatech's patented and exclusive valve system offers consistent firing and optimal depth setting of fasteners. Wide composite base and low center of gravity combine together to offer exceptional stability. It's short lenght allows installation of boards closer to the end wall.



Features

- L or T nail configuration available
- mounted for standard 3/4" (19 mm) solid flooring
- exclusive valve system minimizing tongue splitting by setting nails at optimal depth, independently of the striking force
- requires only 4 lbs (1.8 kg) of swing force to activate
- compact design to get closer to end walls
- large composite base to increase stability and minimize damage to prefinished floors
- exclusive contact safety device activated when tool is positioned on the flooring
- ergonomic comfort grip handle
- quick loading magazine with spring loaded nail pusher
- 2.8 lbs (1.3 kg) non marring mallet included

Options

- L or T nail conversion kit
- adapter plate for various profiles of solid flooring
- tool kit, carrying case
- "Trak-Edge" nailer shoe, specifically designed to install square & micro-bevel factory finished products without damaging top edge
- 200 & 300 cleats magazine

Applications

• 3/4" (19 mm) standard solid hardwood flooring 1/2" to 33/32" (13 to 26 mm) applications require optional adapter plate.

Tool Specifications

WEIGHT: 12 lbs (5.5 kg) HEIGHT: 17 3/4" (451 mm) LENGTH: 16 3/4" (365 mm) CAPACITY: 110 nails OPERATING PRESSURE: 90 psi

Fasteners Specifications

L CLEATS, 16 gage I 1/2", I 3/4", 2" (38, 45, 50 mm) T CLEATS, 16 gage I 1/2", 2" (38, 50 mm)

Stainless steel cleats also available

Cleat nails minimize wood splitting and still allow for expansion and contraction of flooring material.



1135, de Lorraine Quebec City, Quebec Canada GIJ 1R8

Tel.: I (418) 522-7744

USA / CAN:

1 (800) 363-1962 Fax: I (418) 522-7466 sales@primatech.ca www.primatech.ca

Printed in Canada